FireAngel.

CO-9B BATTERY POWERED CO ALARM

Advanced electrochemical Sensor type **Battery type** 2 x 1.5v AA alkaline batteries Advanced electrochemical sensor calibrated and tested in CO gas. · Alarm to be installed near any fuel-burning FireAngel appliance. • Easy to install. Automatic self diagnostic check. • 7 year warranty. Includes 2x 1.5V AA alkaline batteries. • Test button - to test circuitry and sounder. • End of life indication. \heartsuit CE BS EN50291-1:2010+A1:2012 BS EN50291-2:2010 Licence No: KM 551504 **Technical Specification** 109mm 109mm (width) x 67mm (height) Dimensions x 38mm (depth) 7mm Supply voltage 3V DC Technology Advanced electrochemical Alarm sound level 85dB(A) at 1m (minimum) Installation positions Wall / Free-standing **Operating temperature** -10°C to +40°C 30% to 90% RH non-condensing **Operating humidity Storage temperature** -20°C to +60°C **Storage humidity** 30% to 90% RH non-condensing ABS, UL94 VO fire retardant **Plastic material** Warranty 7 years Weight 125g **Certified to** BS EN50291-1:2010+A1:2012 and BS EN50291-2:2010 Independently tested to N/A Maximum number of connected units N/A

For further information or sales enquires: www.fireangel.co.uk

N/A N/A

Operating frequency

Range

www.butlertechnik.com